

Cecil County Fair

Modified Gas Class

6500lbs maximum with driver

1. Suspension modifications are permitted. Fully welded suspension and trussed rears permitted.
2. Hook point cannot extend more than 6" under the truck and must be 30% of the wheelbase and no more the 30 degree angle. Hitch height maximum of 26" on four wheel drive and 30" on two wheel drive, with a minimum of a 3.75" X 3.0" opening. Hitch point must be easily accessed. No "trick" type hitches permitted. Hitch must be stationary in all directions. Hitch must be frame mounted. Hitch may not be mounted forward of the center line of rear axle.
3. Open to any engine combination (does not have to be make specific). Aftermarket blocks permitted.
4. No cast iron clutches or flywheels permitted.
5. Safety kill mandatory and must be installed on the rear of truck. Kill switch will be securely mounted to the back of the vehicle and have a (2) inch diameter ring to attach the sled.
6. No fuel lines or tanks permitted inside of truck cab.
7. Front weights must be no more than 60" from the center line of the front axle to forward most point and be securely fastened. No weights are allowed in cab of truck, if installed in bed of truck they are to be securely fastened to bed of truck.
8. Fuel limited to gasoline, race fuel or alcohol only. No nitrous, propane or any oxygen enhancing agents allowed.
9. Drive train will consist of the following: Any front axle, any transfer case and any rear axle.
10. All trucks must have all hubs covered. Covers don't have to be solid, but must be able contain parts should breakage occur. A hole may be cut to allow locking and unlocking of front hubs if necessary.
11. S.F.I. Bell housing Blankets and /or S.F.I Blow proof Bell housing required.
12. One scatter shield must be on all universal joints beyond the rear of the transmission and the front universal joint at the front differential. Scatter shield must be of a solid construction and be able to contain debris or direct debris toward the ground. One drive shaft loop must be installed on any drive shaft over 36 inches long including those with a carrier bearing.
13. If bed floor and/or tailgate have been removed, they must be covered to contain debris should breakage occur. Canvas covers are acceptable.
14. Dual rear wheels are permitted.
15. Fire Extinguishers, helmets, shoes and seatbelts are required.